

Specialist Wheel & Tyre Service Equipment



Tyre Diagnostics | Tyre Changers | Wheel Balancers | Wheel Aligners

☎ +44 208 498 1288 ✉ sales@sicamtyreequipment.co.uk 🌐 www.sicamtyreequipment.co.uk

181 Forest Road, Hainault, Essex, UK, IG6 3HZ



TYRE CHANGERS

FALCO EVO 620S FALCO EVO 620 S V2



STABILITY AND STRENGTH

New G-frame concept with new, additional structural elements for improved strength. The bead breaker and the base of the pole are welded to the body to improve its strength and solidity over time

FLEXIBILITY

Able to process any kind of car, light commercial vehicle and motorcycle (with special accessory kit) wheels: max wheel diameter 1100 mm and max wheel width 11".

SAFETY

Plastic pole protection with integrated holders for tools and valves

EASY TO USE AND FAST

- Inflating system controlled by gun with manometer [bar/psi]
- Bead breaker shape designed to protect the rim from risk of scratches
- Second speed with pedal selection (FALCO EVO 620)
- New pull-out pedal unit for quick, convenient maintenance
- "SIDE LIFT" available as accessory for all models, maximum comfort and ergonomics

Installation of the Tecnoroller NG helper system enables exceptionallu quick, easy mounting and demounting of any kind of tire, even the most difficult UHP or RFT types.



Technical specifications

FALCO EVO 620S

Mains connections
1 Ph - 230V 50 - 60 Hz
3 Ph - 400 V 50 - 60 Hz
3 Ph - 230 V 50 - 60 Hz
1 Ph - 110V - 60 Hz

External clamping
10" - 22"

Internal clamping
12" - 24"

Rim width
3" - 11"

Max. wheel diameter
1100 mm

Bead breaker range
65 - 305 mm

Air connection
8 -10 bar

Rotation speed
7,5 - 15 rpm

Dimensions max. (H x D x W)
1960 x 1660 x 1350 mm

Pole folded
1860 x 1660 x 1950 mm (V1)

Net weight
230 kg

SCOPE OF DELIVERY

- ▶ 1x Bead lever
- ▶ 1x Lubricant brush
- ▶ 1x Inflating gun system with pipe connections